

ELECTRA IW 1002 Be

Product specification sheet

Magnetic leveled grille ready-to-be-painted
Total integration



Sealed MDF speaker
Traditional speaker behavior
Bass quality and linearity



6.5" (16.5cm) midbass 3rd generation
W cone
Exclusive composite sandwich
Unequaled rigidity and neutrality

Pure Beryllium tweeter
Response up to 40kHz

OPC filtering, phase optimal control
Tweeter level adjustments
Wall Boost Control



- "Made in France"
- True compact alternative to the traditional high-end 2-way loudspeaker
- Easy and quick installation
- Optional On-Wall mounting frame
- Optional mounting kit (for walls under construction)

The optional On-Wall mounting frame broadens the IW 1002 Be mounting possibilities. The whole is 4" (10cm) deep with the integrated wall fixing.

Type	2-way In-Wall sealed speaker
Drivers	6 ¹ / ₂ " (16.5cm) "W" midbass. 1 ¹ / ₄ " (27mm) Be inverted dome tweeter
Frequency response (±3dB)	60Hz - 40kHz
Sensitivity (2.83V/1m)	88dB
Nominal impedance	8 Ω
Recommended amplifier power	25 - 150W
Tweeter adjustment	-3dB / 0dB / +3dB
Crossover frequency	2 600Hz
Frame size: - with grille - without grille	16 ³ / ₄ " x 12 ¹ / ₈ " - (0 ³ / ₁₆ " thick) (425 x 308mm - (4.5mm thick)) 16 ¹ / ₂ " x 11 ³ / ₄ " - (0 ¹ / ₁₆ " thick) (415 x 298mm - (1.5mm thick))
Cut-out dimensions (HxW)	1415/16" x 103/8" (379 x 262mm)
Depth from wall	37/8" (99mm)
Net weight	14.1lb (6.4kg)

The IW 1002 Be's sophisticated design enables it to compete with any high-end loudspeaker thanks to its pure Beryllium inverted dome tweeter and its latest generation W cone woofer loaded with integrated sealed volume. The highest-fidelity in invisible version.



FOCAL
the Spirit of Sound